Institutional and Park Zone

Institutional and Park Zone Regulations (2012-001)

7.12.1 Uses Permitted

See Section 6.

7.12.2 Building Standards (2022-007)			
For all buildings	I	Р	SMF
Minimum required front yard	3.0 m	3.0 m	n/a
Maximum front yard	6.0 m	6.0 m	n/a
Minimum required flankage	3.0 m	3.0 m	n/a
Maximum flankage	6.0 m	6.0 m	n/a
Minimum required interior side yard	1.5 m (1)	n/a (2)	n/a
Minimum required rear yard	7.5 m (3)	7.5 m (3)	n/a
Minimum height (2023-025)	11.0 m (4)	11.0 m	n/a
Maximum height	16.0 m	16.0 m	n/a
Accessory buildings and structures are permitted subject to Section 4.14 of this			


By-law.

Yard encroachments are permitted subject to Section 4.21 of this By-law.


Parking standards are set out in Section 5 of this By-law.

Notes to Section 7.12.2

- Minimum required interior side yard where a building is greater than 16.0 metres in height - 3.0 metres.
- 2.
- Minimum required interior side yard where the interior side yard abuts a lot in the General Urban (GU) or Sub-urban (S) Zone – 1.5 metres.
- Minimum required interior side yard where a building is greater than 16.0 metres in height and where the interior side yard abuts a lot in the General Urban (GU) or Sub-urban (S) Zone - 3.0 metres.
- 3. i) Minimum required rear yard on a lot only accessed by a rear lane -0.75 metres.
 - Minimum required rear yard on a lot abutting lands in the Natural Heritage System (NHS), Cemetery (CE), or Park (P) Zone – 3.0 metres.
- Shall not apply to a commercial school, post-secondary school, private school or public school. (2023-025)



The grey represents potential building area. The internal dashed line represents



Height is measured to the tallest point of a building.

Institutional and Park Zone

7.12.3 Performance Zone Categories – Institutional (I) Zone

7.12.3.1 Institutional Performance (I-1) Zone 1

In addition to the permitted *uses*, *buildings* and regulations of the Institutional (I) *Zone*, a *private school use* and related *buildings* shall be permitted in the Institutional Performance (I-1) *Zone* 1 subject to the regulations of the I *Zone*, with the exception that the maximum *floor space index* shall be 1.5 and any surface parking shall be located in accordance with the following:

- i. Minimum *setback* from the *front lot line*: 4 metres provided that no surface parking shall be permitted between any *building* and the *front lot line* or *flankage*.
- ii. Minimum setback from the *interior side lot line*: 3 metres
- iii. Minimum setback from the flankage: 4 metres
- iv. Minimum *setback* from the *rear lot line* where it abuts a *residential zone*: 7 metres

(I-2 and higher relocated by 2012-001 and 2013-065)